



Automatic Day Tanks

This flexible system allows us to **customize** the control circuitry to *your specifications*, while keeping the cost in line with other non-flexible printed circuit board systems. These system consists of hard wired, socket relays in conjunction with internal float switches and lights mounted on a panel to display and control many different functions.

Standard Features

- Heavy gauge steel lap joint construction
- Heavy duty steel cover w/window
- 6 1/2" square removable inspection plate
- 1 1/2" NPT fuel level gauge
- Heavy duty float switch
- "Press to test" switch
- "Pump-running" indicator light
- Interior - epoxy coated
- Exterior - gray enamel
- 1 1/4" NPT normal vent connection
- Emergency vent connection- size specified by UL-142
- 4 - 1" NPT connections; fuel outlet, fuel return, alternate fuel return, and overflow.
- Heavy duty 1/3 HP, 115 VAC, 1 P, 60 Hz. motor with 2 GPM bronze high lift gear pump with stainless steel shafts
- 3/8" NPT tank drain connection
- All plumbing preconnected
- Hard wired control wiring with socketed, replaceable relays

MODEL	GALLON / LITRE	W x D x H (inches)
PD10ULD	10/38	24 x 12 x 22
PD15ULD	15/57	24 x 12 x 25.5
PD25ULD	25/95	24 x 12 x 33
PD50ULD	50/189	24 x 18 x 42
PD60ULD	60/228	24 x 18 x 47
PD75ULD	75/284	24 x 18 x 55
PD100ULD	100/379	24 x 24 x 55
PD150ULD	150/570	24 x 36 x 55
PD200ULD	200/760	24 x 48 x 59.5
PD275ULD	275/1041	24 x 60 x 59.5
PD300ULD	300/1137	24 x 65 x 59.5
PD325ULD	325/1235	28 x 60 x 59.5
PD350ULD	350/1330	24 x 75 x 59.5
PD400ULD	400/1520	36 x 57 x 59.5
PD450ULD	450/1710	36 x 65 x 59.5
PD500ULD	500/1900	36 x 72 x 59.5
PD550ULD	550/2090	36 x 79 x 59.5
PD600ULD	600/2280	36 x 86 x 59.5
PD700ULD	700/2660	48 x 76 x 59.5
PD800ULD	800/3040	48 x 86 x 59.5
PD900ULD	900/3420	48 x 97 x 59.5
PD1000ULD	1000/3800	48 x 108 x 59.5